


1Y2 Eurocrates


AS 110
REFL 11
POX 11
POY 11
Whitening
Anti-aliasing
Empty
Anti-aliasing
Whitening
AS55
POP 55
REFL 55
REFL 165

REFL 33
POP 22
POP 110
AS 165
Whitening
Anti-aliasing
Empty
Anti-aliasing
Whitening
Common-mode board
LSC-PD interface
Empty
LSC-PD interface
Empty
LSC-PD interface
Empty

SOS De-white
SOS coil driver
SOS coil driver
SOS De-white
SOS coil driver
SOS coil driver
Empty
Whitening
Empty
Empty
Empty
UNUSED
UNUSED
UNUSED
IP-POS / IPANG

Legend

 = LSC Demod board (D99051)

 = LSC Whitening filter (D990694)


 = LSC AA filter (D000076)

 = Common Mode Servo Card (D1500308)

 = LSC PD interface (D990543)

 = SOS De-Whitening (D990543)

 = SOS Coil Driver (D010001)

 = QPD interface module (D030238)

Notes:

1. AS165 and POP 55 LSC demodulator boards are not used currently. The corresponding whitening and AA channels are used for ALS X and Y DFD outputs respectively.
2. SOS de-whitening and coil drivers are used for TT1 and TT2.